

Section name references in L^AT_EX*

Sebastian Rahtz

2007/05/29

Documentation overview for hyperref

The documentation for package `hyperref` consists of several files:

[Manual](#) The **USER MANUAL** (also available as HTML).

[README](#) The **README** file (also available as text file). Here information is collected that is not yet in the manual: new features, package compatibility, limitations, known problems, ...

[ChangeLog](#) This file records the version history (also available as text file).

[Options](#) This file provides a short option summary.

[Bookmark talk, slides](#) Slides for the talk “PDF information and navigation elements with hyperref, pdfTeX and thumbpdf” at EuroT_EX 1999.

[Bookmark talk, paper](#) The paper version of the talk.

Source code documentation:

[hyperref.dtx](#) This is the source code documentation for hyperref.

[backref.dtx](#) “Back referencing from bibliographical citations”

 [nameref.dtx](#) “Section name references in L^AT_EX” (this file)

Contents

| | | |
|----------|--|----------|
| 1 | Introduction | 2 |
| 2 | History | 2 |
| 3 | Implementation | 2 |
| 3.1 | <code>\label</code> stuff | 2 |
| 3.2 | Changes of section macros | 4 |
| 3.2.1 | Class beamer | 5 |
| 3.3 | Referencing stuff | 6 |
| 3.4 | Usage and frontend | 7 |
| 3.5 | Package ifthen support | 7 |
| 3.6 | Compatibility with <code>varioref</code> | 8 |
| 3.7 | Support for listings | 10 |

*This file has version number v2.31, last revised 2007/05/29.

1 Introduction

Cross-referencing to include the *name* of the section, rather than just the number or page. This works by redefining some of the inside L^AT_EX macros, so it is vulnerable to future changes.

2 History

Sebastian Rahtz, for Lou Burnard, March 15th 1994;
 SPQR CERN July 1994;
 Last mod. Sept. 3th MG;
 Sept. 19th SPQR;
 April 11th 1995 SPQR (added section formatting hook);
 April 14th 1995 SPQR (compatibility with hyperref);
 June 22 1995 SPQR (removed typeout from Sectionformat);
 September 22 1997 added varioref hacks by Corey Minyard;
 September 28th changes by David Carlisle.
 More recent changes are recorded in ChangeLog.

3 Implementation

```
1 <*package>
2 \RequirePackage{refcount}[2006/02/12]
```

We redefine `\label` so that it also writes the name of the current section to the .aux file; if the name ends in a dot, we zap it. To allow for the hyperref package, also write fourth and fifth fields (empty by default; used for cross-ref name, and file).

```
3 \def\strip@period#1.\relax#2\@@@{#1}
```

3.1 `\label` stuff

Here is tested, whether package showkeys is loaded. But if option final is used, the macros of showkeys are not defined, so we have to check an additional test.

```
4 \newif\ifNR@showkeys
5 \NR@showkeysfalse
6 \@ifpackageloaded{showkeys}{%
7   \begingroup
8     \@ifundefined{SK@@label}{%
9       }{%
10        \global\NR@showkeystrue
11      }%
12    \endgroup
13  }{}

14 \def\label#1{%
15   \@bsphack
16   \begingroup
17     \@onelevel@sanitize\@currentlabelname
18     \edef\@currentlabelname{%
19       \expandafter\strip@period\@currentlabelname\relax.\relax\@@@%
20     }%
```

```

21 \protected@write\@auxout{}\{%
22 \string\newlabel{#1}\{%
23 {\@currentlabel}%
24 {\thepage}%
25 {\@currentlabelname}%
26 {\@currentHref}\}%
27 }%
28 }%
29 \endgroup
30 \esphack
31 }%
32 \ifNR@showkeys
33 \def\label#1{%
34 \bsphack
35 \SK@SK@@label{#1}%
36 \begingroup
37 \@onelevel@sanitize\@currentlabelname
38 \edef\@currentlabelname{%
39 \expandafter\strip@period\@currentlabelname\relax.\relax\@@@%
40 }%
41 \protected@write\@auxout{}\{%
42 \string\newlabel{#1}\{%
43 {\@currentlabel}%
44 {\thepage}%
45 {\@currentlabelname}%
46 {\@currentHref}\}%
47 }%
48 }%
49 \endgroup
50 \esphack
51 }%
52 \fi
53 \let\ltx@label\label

```

Needed for the *subeqnarray* package.

```

54 \@ifundefined{slabel}\{\}%
55 \def\slabel#1{%
56 \bsphack
57 \if@filesw
58 {%
59 \@onelevel@sanitize\@currentlabelname
60 \edef\@currentlabelname{%
61 \expandafter\strip@period\@currentlabelname\relax.\relax\@@@%
62 }%
63 \let\thepage\relax
64 \def\protect{\noexpand\noexpand\noexpand}%
65 \edef\@tempa{%
66 \write\@auxout{%
67 \string\newlabel{#1}\{%
68 {\thesubequation}%
69 {\thepage}%
70 {\@currentlabelname}%
71 {\@currentHref}\}%
72 }%
73 }%
74 }%
75 \expandafter

```

```

76     }%
77     \@tempa
78     \if@nobreak\ifvmode\nobreak\fi\fi
79     \fi
80     \@esphack
81 }%
82 }

```

Overload an AMS L^AT_EX command, which uses `\newlabel`. Sigh!

```

83 \def\@writetocindent@{%
84   \begingroup
85   \@for\@tempa:=-1,0,1,2,3\do{%
86     \immediate\write\@auxout{%
87       \string\newlabel{tocindent\@tempa}{%
88         \csname r@tocindent\@tempa\endcsname}{-}{-}{-}%
89     }%
90   }%
91 }%
92 \endgroup
93 }

```

3.2 Changes of section macros

Add to the underlying section heading macros so that they note the section name for use by label.

If a section heading or the like has a `\label` in it, we need to extract it, or subsequent processing breaks. This is done by the label-writing routine.

First the numbered sections. While we are about it, put in a useful section formatting macro.

```

94 \let\NR@ssect\@ssect
95 \newcounter{section@level}
96 \def\@sect#1#2#3#4#5#6[#7]#8{%
97   \setcounter{section@level}{#2}%
98   \def\@currentlabelname{#7}%
99   \NR@ssect{#1}{#2}{#3}{#4}{#5}{#6}[#7]{\Sectionformat{#8}{#2}}%
100 }

```

and now the unnumbered ones

```

101 \let\NR@ssect\@ssect
102 \def\@ssect#1#2#3#4#5{%
103   \def\@currentlabelname{#5}%
104   \NR@ssect{#1}{#2}{#3}{#4}{\Sectionformat{#5}{#1}}%
105 }

```

Parts and chapters are treated differently. sigh.

```

106 \let\NR@part\@part
107 \def\@part[#1]#2{%
108   \def\@currentlabelname{#1}%
109   \NR@part[#1]{#2}%
110 }
111 \let\NR@chapter\@chapter
112 \def\@chapter[#1]#2{%
113   \def\@currentlabelname{#1}%
114   \NR@chapter[#1]{#2}%
115 }
116 \let\NR@schapter\@schapter
117 \def\@schapter#1{%
118   \def\@currentlabelname{#1}%

```

```

119 \NR@schapter{#1}%
120 }

Captions

121 \let\NR@@caption\@caption
122 \long\def\@caption#1[#2]{%
123   \def\@currentlabelname{#2}%
124   \NR@@caption{#1}[{#2}]%
125 }

126 \AtBeginDocument{%
127   \@ifpackageloaded{longtable}{%
128     \let\NRorg@LT@c@ption\LT@c@ption
129     \def\LT@c@ption#1[#2]#3{%
130       \NRorg@LT@c@ption{#1}[{#2}]{#3}%
131       \def\@tempa{#2}%
132       \ifx\@tempa\@empty
133         \else
134           \def\@currentlabelname{#2}%
135         \fi
136       }%
137     }{}%
138 }

Compatibility for package titlesec.

139 \AtBeginDocument{%
140   \@ifpackageloaded{titlesec}{%
141     \let\NRorg@ttl@sect@i\ttl@sect@i
142     \def\ttl@sect@i#1#2[#3]#4{%
143       \def\@currentlabelname{#4}%
144       \NRorg@ttl@sect@i{#1}{#2}[{#3}]{#4}%
145     }%
146   }{}%
147 }

```

3.2.1 Class beamer

```

148 \@ifclassloaded{beamer}{%
149   \def\NR@PatchBeamer#1{%
150     \expandafter\let\csname NRorg@beamer@#1\expandafter\endcsname
151       \csname beamer@#1\endcsname
152     \begingroup
153       \edef\x{\endgroup
154         \long\def\expandafter\noexpand\csname beamer@#1\endcsname
155           [####1]{% hash-ok
156             \def\@currentlabelname{####1}%
157             \expandafter\@currentlabelname\csname NRorg@beamer@#1\endcsname
158             [{####1}]%
159           }%
160         }%
161       \x
162     }%
163   \NR@PatchBeamer{section}%
164   \NR@PatchBeamer{subsection}%
165   \NR@PatchBeamer{subsubsection}%
166 }{}

```

3.3 Referencing stuff

We default the label and hypertext reference to be empty.

```
167 \def\@currentlabelname{}
168 \def\@currentHref{}
```

Since the second part of the preserved reference now has five parts (number, page, name, hypertext reference and file), we need extra utility macros:

```
169 \long\def\@firstoffive#1#2#3#4#5{#1}
170 \long\def\@secondoffive#1#2#3#4#5{#2}
171 \long\def\@thirdoffive#1#2#3#4#5{#3}
172 \long\def\@fourthoffive#1#2#3#4#5{#4}
173 \long\def\@fifthoffive#1#2#3#4#5{#5}
```

We have to redefine `\ref` and `\pageref` to know about extra reference elements. Make them robust, and compatible with Babel. The Babel switch is mimicked if not already defined. Some support for package `showkeys` is implemented. If option `notref` of that package is set, `\SK@ref` has the meaning of `\@empty`.

```
174 \providecommand*\@safe@activetrue{}%
175 \providecommand*\@safe@activesfalse{}%
176 \def\NR@setref#1{%
177   \begingroup
178     \@safe@activetrue
179     \expandafter
180   \endgroup
181   \expandafter\NR@@setref\csname r@#1\endcsname
182 }
183 \def\NR@@setref#1{%
184   \ifx\@undefined#1%
185     \let#1\relax
186   \fi
187   \@setref#1%
188 }
189 \def\T@ref#1{%
190   \NR@setref{#1}\@firstoffive{#1}%
191 }%
192 \def\T@pageref#1{%
193   \NR@setref{#1}\@secondoffive{#1}%
194 }%
195 \ifNR@showkeys
196   \ifx\SK@ref\@empty
197     \else
198       \def\T@ref#1{%
199         \@safe@activetrue
200         \SK@\SK@@ref{#1}%
201         \@safe@activesfalse
202         \NR@setref{#1}\@firstoffive{#1}%
203       }%
204       \def\T@pageref#1{%
205         \@safe@activetrue
206         \SK@\SK@@ref{#1}%
207         \@safe@activesfalse
208         \NR@setref{#1}\@secondoffive{#1}%
209       }%
210     \fi
211   \fi
```

Package `hyperref` uses its own definitions of `\ref` and `\pageref` because it extends the syntax by the star form. `\DeclareRobustCommand` is used by `hyperref`.

Package `nameref` can be loaded before, after `hyperref` or after `hyperref`'s definitions in `\AtBeginDocument`.

```
212 \@ifpackageloaded{hyperref}{%
213 }{%
214   \DeclareRobustCommand{\ref}{\T@ref}%
215   \DeclareRobustCommand{\pageref}{\T@pageref}%
216 }
```

3.4 Usage and frontend

Access the (third) name part with `\nameref`;

```
217 \def\T@nameref#1{%
218   \begingroup
219     \let\label\@gobble
220     \NR@setref{#1}\@thirdoffive{#1}%
221   \endgroup
222 }%
223 \ifNR@showkeys
224   \ifx\SK@ref\@empty
225   \else
226     \def\T@nameref#1{%
227       \@safe@activestrue
228       \SK@\SK@@ref{#1}%
229       \@safe@activesfalse
230       \begingroup
231         \let\label\@gobble
232         \NR@setref{#1}\@thirdoffive{#1}%
233       \endgroup
234     }%
235   \fi
236 \fi
237 \def\nameref{\protect\T@nameref}
```

An extended form which gives title and page number.

```
238 \def\Nameref#1{'\nameref{#1}' on page~\pageref{#1}}
```

The default for `\Sectionformat`

```
239 \providecommand\Sectionformat[2]{#1}
```

3.5 Package `ifthen` support

Package `ifthen`'s `\isodd` does not work with `\pageref` because of the extra link and the star form. Therefore we need an expandable variant.

Unfortunately there is no hook in `\ifthenelse` in order to provide expandable versions without link of `\ref` and `\pageref`. As possible target I could only find `\begingroup`:

```
240 \@ifpackageloaded{ifthen}{%
241   \let\NR@Org@ifthenelse@ifthenelse
242   \def\ifthenelse{%
243     \let\begingroup\NR@TE@begingroup
244     \NR@Org@ifthenelse
245   }%
246   \let\NR@Org@begingroup\begingroup
247   \def\NR@TE@begingroup{%
248     \let\begingroup\NR@Org@begingroup
249     \begingroup
250     \def\ref##1{\getrefbykeydefault{##1}{}{??}}%
251   }
```

```

251 \def\pageref##1{\getrefbykeydefault{##1}{page}{0}}%
252 }%
253 {}

```

3.6 Compatibility with varioref

[This section was derived by Corey Minyard minyard@acm.org from the varioref package]

```

254 \AtBeginDocument{%
255   \ifx\csname @vppageref\endcsname\relax
256   \else
257     \def\@vppageref#1[#2]#3{%
258       \begingroup
259         \csname @safe@activestrue\endcsname
260         \edef\x{#3}%
261         \@onelevel@sanitize\x
262         \toks@{%
263           \NR@vppageref{#1}[{#2}]%
264         }%
265         \edef\x{\endgroup
266           \the\toks@{\x}%
267         }%
268       \x
269     }%
270     \def\NR@vppageref#1[#2]#3{%
271       \leavevmode\unskip
272       \global\advance\c@vrcnt\@ne
273       \@ifundefined{r@the\c@vrcnt @vr}%
274       {\@namedef{r@the\c@vrcnt @vr}{\{??\}{??}\{-\}\{-\}\{-\}\{-\}}}%
275       \edef\@tempa{%
276         \expandafter\expandafter\expandafter
277         \@secondoffive\csname r@the\c@vrcnt @vr\endcsname
278       }%
279       \@ifundefined{r@the\c@vrcnt @xvr}%
280       {\@namedef{r@the\c@vrcnt @xvr}{\{??\}{??}\{-\}\{-\}\{-\}\{-\}}}%
281       \edef\@tempb{%
282         \expandafter\expandafter\expandafter
283         \@secondoffive\csname r@the\c@vrcnt @xvr\endcsname
284       }%
285       {%
286         \let\@currentlabel\@empty
287         \expandafter\label\expandafter{\the\c@vrcnt @xvr}%
288       }%
289       \ifx\@tempa\@tempb
290       \else
291         \vref@err{%
292           \noexpand\vref at page boundary %
293           \@tempb-\@tempa\space (may loop)%
294         }%
295       \fi
296       \@ifundefined{r@#3}{\@namedef{r@#3}{\{??\}{??}\{-\}\{-\}\{-\}\{-\}}}%
297       \edef\thevppagerefnum{%
298         \expandafter\expandafter\expandafter
299         \@secondoffive\csname r@#3\endcsname
300       }%
301       \ifx\vref@space\@undefined
302         \space

```



```

303 \else
304 \vref@space
305 \fi
306 \ifx\@tempa\thepagerefnum
307 #1%
308 \else
309 #2%
310 \is@pos@number\thepagerefnum{%
311 \is@pos@number\@tempa{%
312 \@tempcnta\@tempa
313 \advance\@tempcnta\@ne
314 }{%
315 \@tempcnta\maxdimen
316 }%
317 \ifnum \thepagerefnum =\@tempcnta
318 \ifodd\@tempcnta
319 \if@twoside
320 \ref@text@face@after
321 \else
322 \ref@text@after
323 \fi
324 \else
325 \ref@text@after
326 \fi
327 \else
328 \advance\@tempcnta-2 %
329 \ifnum \thepagerefnum =\@tempcnta
330 \ifodd\@tempcnta
331 \ref@text@before
332 \else
333 \if@twoside
334 \ref@text@face@before
335 \else
336 \ref@text@before
337 \fi
338 \fi
339 \else
340 \ref@text@faraway{#3}%
341 \fi
342 \fi
343 }{%
344 \ref@text@faraway{#3}%
345 }%
346 \fi
347 {%
348 \let\@currentlabel\@empty
349 \expandafter\label\expandafter{\the\c@vrcnt @vr}%
350 }%
351 }%
352 \DeclareRobustCommand\vnameref[1]{%
353 \unskip~\nameref{#1}%
354 \@vpageref[\unskip]{#1}%
355 }%
356 \fi
357 }

358 \ifundefined{@Refstar}{%
359 \def\T@Ref#1{%

```

```

360 \NR@setref{#1}\NR@MakeUppercaseFirstOfFive{#1}%
361 }%
362 \def\NR@MakeUppercaseFirstOfFive#1#2#3#4#5{%
363 \MakeUppercase#1%
364 }%
365 }{}%
366 \AtBeginDocument{%
367 \ifpackageloaded{varioref}{%
368 \ifundefined{@Refstar}{%
369 \DeclareRobustCommand*\Ref}[1]{%
370 \T@Ref{#1}%
371 }%
372 }{}%
373 }{}%
374 }%

```

3.7 Support for listings

```

375 \AtBeginDocument{%
376 \ifpackageloaded{listings}{%
377 \let\NR@Org@lst@MakeCaption\lst@MakeCaption
378 \def\lst@MakeCaption{%
379 \ifx\lst@label\@empty
380 \else
381 \let\@currentlabelname\lst@@caption
382 \fi
383 \NR@Org@lst@MakeCaption
384 }%
385 }{}%
386 }
387 </package>

```

4 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

| Symbols | 118, 123, 134, | 279, 296, 358, 368 |
|------------------------------|------------------|-------------------------------|
| \@@@ | 3, 19, 39, 61 | 143, 156, 167, 381 |
| \@@vpageref | 257 | \@namedef . 274, 280, 296 |
| \@auxout | 21, 41, 66, 86 | \@empty . . . 132, 196, |
| \@bsphack | 15, 34, 56 | 224, 286, 348, 379 |
| \@caption | 121, 122 | \@esphack . . . 30, 50, 80 |
| \@chapter | 111, 112 | \@fifthoffive 173 |
| \@currentHref | 26, 46, 71, 168 | \@firstoffive |
| \@currentlabel | 23, 43, 286, 348 | 169, 190, 202 |
| \@currentlabelname | 17, | \@for 85 |
| 18, 19, 25, 37, | | \@fourthoffive 172 |
| 38, 39, 45, 59, | | \@gobble 219, 231 |
| 60, 61, 70, 98, | | \@ifclassloaded . . . 148 |
| 103, 108, 113, | | \@ifpackageloaded |
| | | 6, 127, 140, |
| | | 212, 240, 367, 376 |
| | | \@ifundefined |
| | | 8, 54, 273, |
| | | \@one 272, 313 |
| | | \@onelevel@sanitize |
| | | 17, 37, 59, 261 |
| | | \@part 106, 107 |
| | | \@safe@activesfalse |
| | | 175, 201, 207, 229 |
| | | \@safe@activetrue |
| | | 174, |
| | | 178, 199, 205, 227 |
| | | \@schapter 116, 117 |
| | | \@secondoffive |
| | | 170, 193, |
| | | 208, 277, 283, 299 |
| | | \@sect 94, 96 |
| | | \@setref 187 |

| | | | |
|---|--------------------|-------------------------------------|--|
| <code>\@ssect</code> | 101, 102 | 60, 65, 153, 260, | 243, 246, 248, |
| <code>\@tempa</code> | 65, 77, | 265, 275, 281, 297 | 286, 348, 377, 381 |
| | 85, 87, 88, 131, | <code>\else</code> | <code>\long</code> |
| | 132, 275, 289, | 133, | 122, 154, 169, |
| | 293, 306, 311, 312 | 197, 225, 256, | 170, 171, 172, 173 |
| <code>\@tempb</code> | 281, 289, 293 | 290, 303, 308, | <code>\lst@caption</code> |
| <code>\@tempcnta</code> | 312, | 321, 324, 327, | <code>\lst@label</code> |
| | 313, 315, 317, | 332, 335, 339, 380 | <code>\lst@MakeCaption</code> |
| | 318, 328, 329, 330 | <code>\endcsname</code> | 377, 378 |
| <code>\@thirdoffive</code> | | 150, 151, 154, | <code>\LT@caption</code> |
| | 171, 220, 232 | 157, 181, 255, | <code>\ltx@label</code> |
| <code>\@undefined</code> | 184, 301 | 259, 277, 283, 299 | 53 |
| <code>\@vpageref</code> | 354 | <code>\endgroup</code> | M |
| <code>\@writetocindent</code> | 83 | 12, | <code>\MakeUppercase</code> |
| | | 29, 49, 92, 153, | 363 |
| | | 180, 221, 233, 265 | <code>\maxdimen</code> |
| | | <code>\expandafter</code> | 315 |
| | | . 19, 39, 61, 75, | N |
| A | | 150, 154, 157, | <code>\Nameref</code> |
| <code>\advance</code> | 272, 313, 328 | 179, 181, 276, | 238 |
| <code>\AtBeginDocument</code> | 126, | 282, 287, 298, 349 | <code>\nameref</code> |
| | 139, 254, 366, 375 | | 237, 238, 353 |
| | | | <code>\newcounter</code> |
| | | | 95 |
| | | | <code>\newif</code> |
| | | | 4 |
| | | | <code>\newlabel</code> |
| | | | 22, 42, 67, 87 |
| B | | | <code>\nobreak</code> |
| <code>\begingroup</code> | 7, 16, | | 78 |
| | 36, 84, 152, 177, | | <code>\noexpand</code> |
| | 218, 230, 243, | | 64, |
| | 246, 248, 249, 258 | | 154, 156, 157, 292 |
| | | | <code>\NR@caption</code> |
| | | | 121, 124 |
| | | | <code>\NR@setref</code> |
| | | | 181, 183 |
| | | | <code>\NR@vpageref</code> |
| | | | 263, 270 |
| | | | <code>\NR@chapter</code> |
| | | | 111, 114 |
| C | | | <code>\NR@MakeUppercaseFirstOfFive</code> |
| <code>\c@vrcnt</code> | 272, 273, | | |
| | 274, 277, 279, | | 360, 362 |
| | 280, 283, 287, 349 | | <code>\NR@part</code> |
| <code>\csname</code> | 88, | | 106, 109 |
| | 150, 151, 154, | | <code>\NR@PatchBeamer</code> |
| | 157, 181, 255, | | 149, 163, 164, 165 |
| | 259, 277, 283, 299 | | <code>\NR@chapter</code> |
| | | | 116, 119 |
| | | | <code>\NR@ssect</code> |
| | | | 94, 99 |
| | | | <code>\NR@setref</code> |
| | | | 176, |
| | | | 190, 193, 202, |
| | | | 208, 220, 232, 360 |
| | | | <code>\NR@showkeysfalse</code> |
| | | | 5 |
| | | | <code>\NR@showkeystrue</code> |
| | | | 10 |
| | | | <code>\NR@ssect</code> |
| | | | 101, 104 |
| | | | <code>\NR@TE@begingroup</code> |
| | | | 243, 247 |
| | | | <code>\NR@Org@begingroup</code> |
| | | | 246, 248 |
| | | | <code>\NR@Org@ifthenelse</code> |
| | | | 241, 244 |
| | | | <code>\NR@Org@lst@MakeCaption</code> |
| | | | |
| | | | 377, 383 |
| | | | <code>\NR@Org@LT@caption</code> |
| | | | 128, 130 |
| | | | <code>\NR@Org@ttl@ssect@i</code> |
| | | | 141, 144 |
| | | | P |
| | | | <code>\pageref</code> |
| | | | 215, 238, 251 |
| | | | <code>\protect</code> |
| | | | 64, 237 |
| | | | <code>\protected@write</code> |
| | | | 21, 41 |

| | | |
|---|---|--|
| <code>\providecommand</code> . . . | <code>\SK@@label</code> 35 | <code>\thevpagerefnum</code> 297, |
| 174, 175, 239 | <code>\SK@@ref</code> . . 200, 206, 228 | 306, 310, 317, 329 |
| R | <code>\SK@ref</code> 196, 224 | <code>\toks@</code> 262, 266 |
| <code>\Ref</code> 369 | <code>\slabel</code> 55 | <code>\ttl@sect@i</code> . . . 141, 142 |
| <code>\ref</code> 214, 250 | <code>\space</code> 293, 302 | U |
| <code>\reftextafter</code> . 322, 325 | <code>\string</code> . . 22, 42, 67, 87 | <code>\unskip</code> . . . 271, 353, 354 |
| <code>\reftextbefore</code> 331, 336 | <code>\strip@period</code> | |
| <code>\reftextfaceafter</code> . 320 | 3, 19, 39, 61 | V |
| <code>\reftextfacebefore</code> . 334 | | <code>\vnameref</code> 352 |
| <code>\reftextfaraway</code> 340, 344 | T | <code>\vref</code> 292 |
| <code>\relax</code> 3, 19, | <code>\T@nameref</code> 217, 226, 237 | <code>\vref@err</code> 291 |
| 39, 61, 63, 185, 255 | <code>\T@pageref</code> 192, 204, 215 | <code>\vref@space</code> . . . 301, 304 |
| <code>\RequirePackage</code> 2 | <code>\T@Ref</code> 359, 370 | |
| S | <code>\T@ref</code> 189, 198, 214 | W |
| <code>\Sectionformat</code> | <code>\the</code> 266, 273, | <code>\write</code> 66, 86 |
| 99, 104, 239 | 274, 277, 279, | |
| <code>\setcounter</code> 97 | 280, 283, 287, 349 | X |
| <code>\SK@</code> . . . 35, 200, 206, 228 | <code>\thepage</code> . 24, 44, 63, 69 | <code>\x</code> . . . 153, 161, 260, |
| | <code>\thesubequation</code> . . . 68 | 261, 265, 266, 268 |